



STANDARD FEATURES

Model: KABAIR 14-E, DC Powered Air Conditioner

Product Name: DC powered air conditioner

Driven Type: Battery Powered Driven

Installation: Rooftop mounted & mono-block

Compressor: 15cc/r or 18cc/r

Application: Trucks, commercial vehicles and electric vehicles

SPECIFICATIONS

Model		Specs		
KA14-AE		-5°C (23°F)	5500 BTU/H	1620W
KA14-BE		-10°C (50°F)	5000 BTU/H	1450W
Temperature rating in container		-15°C ~ +25°C (5°F to 77°F)		
Control voltage		DC12V		
	Priven method	Split & front mounted and battery driven unit, build-in DC compressor		
Suitable refrigerated cargo box (m³)		8 ~ 12m³ (280 to 425ft³)		
Defrosting function		R404a Hot gas defrost (Auto./Man.)		
Build-in Compressor		15cc/r, 18cc/r or 26cc/r		
Refrigerant		R134a/R404a, 1.5~1.7kg		
Heating function		Optional		
Controller		Electronic digital controller		
Dimensions (mm)	Evaporator	1020x648x220 (40.16x25.51x8.66 inch)		
	Condenser	1178x585x403 (46.38x23.03x15.86 inch)		
Applicable refrigerated truck body		2 to 8m (9,51~13,78 ft)		
Compressor voltage		DC12V / 24V / 48V / 60V / 72V etc.		