



**EASY  
INSTALLATION**



**FULL  
DIGITAL CONTROL**



**STANDARD FEATURES**

**Model :** KABAIR 8RT-E, Battery Powered Refrigeration Unit

**Driven Type :** Battery Powered Driven

**Refrigerant :** R134a/R404a, 0.5kg~0.6kg

**Compressor :** 15cc/r, 18cc/r or 26cc/r

**Installation :** Split Design, build-in DC compressor

**Application :** Small refrigerated vans & electric cargo vehicles

**SPECIFICATIONS**

Model	Specs
KA8-ARTE	-5°C (23°F)   3753 BTU/H   1100W
KA8-BRTE	-10°C (50°F)   3400 BTU/H   1000W
Temperature rating in container	-15°C ~ +25°C (5°F to 77°F)
Control voltage	DC12V
Driven method	Split & rooftop mounted and battery driven unit, build-in DC compressor
Applicable refrigerated truck body	2 ~ 2.6m (6.56ft to 8.6ft )
Defrosting function	R404a Hot gas defrost (Auto./Man.)
Build-in Compressor	15cc/r, 18cc/r or 26cc/r
Refrigerant	R134a/R404a, 0.6 ~0.8kg
Heating function	Optional
Controller	Electronic digital controller
Dimensions (mm)	Evaporator
	Condenser
Suitable vehicle	Refrigerated cargo vans
Compressor voltage	DC12V / 24V / 48V / 60V / 72V etc.